

# Filters & replacement schedules

A10, A20 RO and earlier A20-B UF - match installed cartridge labels

## A10 - PAC / UF / CB

| Filter | Cartridge                             | Replace every |
|--------|---------------------------------------|---------------|
| PAC    | Composite activated carbon cartridge  | 6 months      |
| UF     | Ultrafiltration membrane cartridge    | 6 months      |
| CB     | Compressed activated carbon cartridge | 6 months      |

Recommended intervals supplied by AquaAloha, October 2026. Each of the three water cartridges is replaced every six months.

## A20 - RO version

| Filter | Cartridge                            | Replace every |
|--------|--------------------------------------|---------------|
| PPF    | PP sediment cartridge                | 6 months      |
| GAC    | Granular activated carbon pre-filter | 6 months      |
| T33    | Activated carbon post-filter         | 6 months      |
| RO     | Reverse-osmosis membrane             | 12 months     |
| BIO    | Mineralization cartridge             | 12 months     |

Five-cartridge RO configuration supplied by AquaAloha, October 2026. These labels differ from the earlier UF layout.

# Earlier A20-B UF reference

Use only for equipment with the matching installed cartridge labels.

| Filter | Cartridge                           | Replace every |
|--------|-------------------------------------|---------------|
| SFT    | Softening cartridge                 | 6 months      |
| PPF    | Sediment cartridge                  | 6 months      |
| GAC    | Granular activated carbon cartridge | 6 months      |
| ELE    | Electropositive membrane cartridge  | 6 months      |
| UF     | Ultrafiltration membrane            | 12 months     |

## Earlier UF manual service references

Air-filter reminder: every 3 months, adjusted for contamination. LED-UV components: every 18 months, with qualified service. These are earlier A20-B manual references and are not universal intervals for the RO version.

## Ordering & routine maintenance

Send the equipment nameplate, cartridge labels, connector type and filter count to AquaAloha before ordering. Recommended intervals can shorten with air quality, use and operating conditions.

Disconnect power before opening the filter compartment. Follow the unit-matched replacement direction, flushing procedure and reminder reset. Clean or wash an air filter only if its instructions permit it; water cartridges are replaced.

## Packing references

A10: three water cartridges plus an air filter; supplied full-set size 210 × 87 × 200 mm and weight 850 g. Earlier A20 packing reference: five cartridges without an air filter, the same dimensions and estimated weight about 1.42 kg. The A20 RO set has not yet been confirmed against these packing figures. Obtain actual gross shipment data before requesting freight.

Confirm the ordered model, electrical nameplate, filtration revision, installation and current availability with AquaAloha before procurement.